



YARD MARVEL

MOTOR RAKE FEATURES



- Handlebars fold for easy transport
- Disengaging clutch
- Easily accessible adjustable height
- Heavy duty wheels all around
- Reel is easily removed for reversing blades for new sharp edge
- Individual Shafts easily accessible thru unique center shaft disk
- Forward movement of reel helps propel the machine
- Flail blade standard
- Optional slicer reel available

SPECIFICATIONS

Engine Options

Briggs & Stratton 5.5 HP Intek ProOHV
Honda 5.5 HP GX OHV

Clutch

Spring loaded belt tightener

Handlebar

Folding 1/2" B.I.P.

Dimensions

Width 25-1/2"
Length 30"
Height (folded) 22-1/2"
Dethatching width 18-1/4"

Blades

48/set 4-3/8 x 1 x 1/8"
Full hard chrome alloy spring steel

Slicer Blades

22 sickle knife sections, heat treated

Blade Shafts

Case hardened cold rolled
1/2" dia x 9-3/8"

Bearings

Heavy duty self centering sealed
flanged ball bearings with zerk fittings

Drive Pulley

Precision milled heavy duty
7" x 1-1/4"

Drive Belt

Heavy duty reinforced cog belt,
"B" width V-type

Front Tires (steel hubs)

8 x 1.75 Semi-pneumatic grooved
tread, sealed replaceable ball bearings

Rear Tires

10 x 1.75 Semi-pneumatic grooved
tread, steel hubs - sintered iron bushing

Rake Deck

Formed & welded 12 GA (7/64")
steel plate deck is isolated from
engine vibration.
Full support side deck

Rear Deck Flap (rubber apron)

1/8" reinforced neoprene
1/8" x 7-3/4" x 19-7/8"

Height Adjustment

Extension knob available
3/4" at rear wheels
1-1/2" at tension spring-height
adjustment box



Rake
With
Handle
Folded



Rake
Bottom
View



Rake
Slicer
Reel
Assembly
(optional)

Yard Marvel Manufacturing Company, Inc. • North 5509 Market Street • Spokane, WA 99208 USA

Phone: (509) 487-2428 • Toll-free: (800) 547-9273 (YARD) • Fax: (509) 483-2044

Web: www.yardmarvel.com • email: info@yardmarvel.com