



# YARD MARVEL

## MOTOR RAKE FEATURES



- Handlebars fold for easy transport
- Disengaging clutch
- Easily accessible adjustable height
- Heavy duty wheels all around
- Reel is easily removed for reversing blades for new sharp edge
- Individual Shafts easily accessible thru unique center shaft disk
- Forward movement of reel helps propel the machine
- Flail blade standard
- Optional slicer reel available

### SPECIFICATIONS

#### Engine Options

Briggs & Stratton 5.5 HP Intek ProOHV  
Honda 5.5 HP GX OHV

#### Clutch

Spring loaded belt tightener

#### Handlebar

Folding 1/2" B.I.P.

#### Dimensions

Width 25-1/2"  
Length 30"  
Height (folded) 22-1/2"  
Dethatching width 18-1/4"

#### Blades

48/set 4-3/8 x 1 x 1/8"  
Full hard chrome alloy spring steel

#### Slicer Blades

22 sickle knife sections, heat treated

#### Blade Shafts

Case hardened cold rolled  
1/2" dia x 9-3/8"

#### Bearings

Heavy duty self centering sealed  
flanged ball bearings with zerk fittings

#### Drive Pulley

Precision milled heavy duty  
7" x 1-1/4"

#### Drive Belt

Heavy duty reinforced cog belt,  
"B" width V-type

#### Front Tires (steel hubs)

8 x 1.75 Semi-pneumatic grooved  
tread, sealed replaceable ball bearings

#### Rear Tires

10 x 1.75 Semi-pneumatic grooved  
tread, steel hubs - sintered iron bushing

#### Rake Deck

Formed & welded 12 GA (7/64")  
steel plate deck is isolated from  
engine vibration.  
Full support side deck

#### Rear Deck Flap (rubber apron)

1/8" reinforced neoprene  
1/8" x 7-3/4" x 19-7/8"

#### Height Adjustment

Extension knob available  
3/4" at rear wheels  
1-1/2" at tension spring-height  
adjustment box



Rake  
With  
Handle  
Folded



Rake  
Bottom  
View



Rake  
Slicer  
Reel  
Assembly  
(optional)

Yard Marvel Manufacturing Company, Inc. • North 5509 Market Street • Spokane, WA 99208 USA

Phone: (509) 487-2428 • Toll-free: (800) 547-9273 (YARD) • Fax: (509) 483-2044

Web: [www.yardmarvel.com](http://www.yardmarvel.com) • email: [info@yardmarvel.com](mailto:info@yardmarvel.com)